

# Alphabetical Index

ITEM	PAGE
<b>A</b>	
Adaptors	
QD	B-8
Taper Bushed	B-18
Alignment, Sprocket	E-65
Area Equivalents	G-25
Area of Circle	G-29
<b>B</b>	
BTU Conversion	G-24
Ball Bearing, Idler Sprocket	A-2
Belt Drives	D-2 – D-126
Bevel Gear Formulas	G-43
Bronze Bearing Idler Sprocket	A-2
Buna-N Spiders	C-20
Bushings	B-2 – B-18
Taper Bushed	B-9 – B-18
QD	B-4 - B-7
<b>C</b>	
Center Distance, Sprockets	E-65, E-68, E-71
Centrifugal Force	G-15
Chain Couplings	C-46 – C-48
Chain Dimensions, Roller	E-60 - E-61
Chain Length Calculation	E-71
Circle Formula	G-29
Circumference of Circles	G-29
Conventional Pulleys	
Groove Dimensions	D-25
Taper Bushed	D-9 – D-22
Couplings	C-3 – C-53
Chain	C-46 – C-48
Comparison	C-4
HRC	C-14 - C-16
Jaw	C-17 – C-22
Martin Flex®	C-5 - C-13
Quadra-Flex®	C-25 – C-45
Coupling Comparison Chart	C-4
Coupling Covers	C-48
Covers, Chain Coupling	C-48

ITEM	PAGE
<b>D</b>	
Decimal and Milimeter Equivalents	G-22
Design Power Chart, Sprocket	E-69
Duplex Sprockets	E-3 - E-55
Dynamic Balancing	D-29
<b>E</b>	
Electrical Formulas	G-9
Engineering Data	
General	G-13
Pulleys	D-24 – D-113
Sprockets	E-56 – E-72
Timing Pulleys	F-33 – F-78
English/Metric Equivalents	G-23 – G-28
<b>F</b>	
Flywheel Formulas	G-15
<b>H</b>	
High Torque Sprockets (HTS)	F-79 – F-169
Hubs Maximum Sprockets	E-62, E-63
Hytrek Spiders	C-20
<b>I</b>	
Idler Sprockets	A-2
Installation	
QD Bushing	B-4 – B-5
Taper Bushing	B-15
Wedge & V Belt Drives	D-32 - D-33
Martin Flex®	C-12
<b>J</b>	
Jaw Couplings	C-17 – C-22
<b>K</b>	
Killowatt Ratings	
HTS Sprockets	F-158 - F-162
Jaw Couplings	C-19
Flex® Coupling	C-31
Timing Pulleys	F-72 – F-77
Killowatt/Torque Formula	G-22
<b>L</b>	
Length Equivalents	G-25
Lubrication, Sprockets	E-65 – E-66

# Alphabetical Index (Continued)

ITEM	PAGE	ITEM	PAGE
<b>M</b>		<b>S</b>	
Made-to-Order Capabilities		Safety Warning & Safety Reminders	
Bushings . . . . .	B-2	on the inside of each section divider.	
Pulleys . . . . .	D-3	Shaft Centers, Sprockets . . . . .	E-69
Specialty Products . . . . .	A-3	Shaft Selection . . . . .	G-14
Sprockets . . . . .	E-2	Simplex Sprockets . . . . .	E-3 – E-55
Timing Pulleys . . . . .	F-2	Speed Ratios . . . . .	E-73
Markets Served . . . . .	2-4	Spiders, Jaw Type . . . . .	C-20
Branch Facilities . . . . .	H-9 – H-11	Buna-N . . . . .	C-20
Martin Flex® Coupling . . . . .	C-5 - C-13	Bronze . . . . .	C-20
Metal Physical Properties . . . . .	G-18	Hytrell . . . . .	C-20
Metric/English Equivalents . . . . .	G-23 - G-28	Urethane . . . . .	C-20
Metric Sprockets . . . . .	E-2 – E-55	Sprockets (Roller Chain) . . . . .	E-5 – E-55
Millimeters Chart . . . . .	G-22	05B . . . . .	E-3
Motor Amps . . . . .	G-9	06B . . . . .	E-4 - E-10
Motor Frame Dimensions . . . . .	G-10	08B . . . . .	E-11 - E-17
<b>N</b>		10B . . . . .	E-18 - E-24
Nema Electrical Enclosure Types . . . . .	G-9	12B . . . . .	E-25 - E-32
Nema Frame Dimensions . . . . .	G-10	16B . . . . .	E-33 - E-48
<b>P</b>		20B . . . . .	E-41 - E-46
Power Equivalents . . . . .	G-24	24B . . . . .	E-47 - E-49
Pulleys . . . . .	D-4 - D-123	28B . . . . .	E-50 - E-52
Drive Selection . . . . .	D-122 – D-123	32B . . . . .	E-53 - E-55
Dynamic Balancing . . . . .	D-29	Diameters . . . . .	E-74 – E-85
Groove Dimensions . . . . .	D-4, – D-24	Double Pitch . . . . .	E-13 – E-17
Installation/Tensioning . . . . .	D-32 – D-33	Engineering Data . . . . .	E-56 – E-85
Nomenclature . . . . .	D-4	Hardening . . . . .	E-70
V-Belt Drive Selection . . . . .	D-1 – D-123	Power Rating . . . . .	E-69
<b>Q</b>		Idler . . . . .	A-4
QD		Index . . . . .	E-1
Bushings . . . . .	B-4 – B-7	Selection Procedure . . . . .	E-65 – E-68
Weld on Hubs . . . . .	B-8	Tooth Dimensions . . . . .	E-64
Quadra-Flex® . . . . .	C-25 – C-40	Stainless Steel Taper Bushings . . . . .	B-14
<b>R</b>		Steel Bushings	
Roller Chain Dimension . . . . .	E-60 - E-61	QD . . . . .	B-6
Roller Chain Lengths . . . . .	E-68, E-71, E-72	Taper Bushing . . . . .	B-13
Rubber Element Jaw Coupling . . . . .	C-20	Steel Properties . . . . .	G-17

# Alphabetical Index

ITEM	PAGE
<b>T</b>	
Taper Bushings .....	B-9 – B-14
Installation/Removal .....	B-9
Reborable .....	B-16
Stainless Steel .....	B-16
Weld-On Hubs .....	B-17
Timing Pulleys .....	F-2 – F-190
Diameters .....	F-36 –F-37
Drive Selection .....	F-114 –F-157
Index .....	F-1
Terminology .....	F-5 – F-7
Trigonometric Functions .....	G-30
Triplex Sprockets .....	E-3 – E-55
<b>U</b>	
Urethane Spiders, Jaw .....	C-20
<b>V</b>	
V-Belt Drives .....	D-2 – D123
V-Belt Drive Selection .....	D-122– D-123
SPA 1-2 Groove .....	D-13
SPA 3-4 Groove .....	D-14
SPA 5-6 Groove .....	D-15
SPB 1-2 Groove .....	D-16
SPB 3-4 Groove .....	D-17
SPB 5-6 Groove .....	D-18
SPB 8-10 Groove .....	D-19
SPC 3-4 Groove .....	D-20
SPC 5-6 Groove .....	D-21
SPC 8-10 Groove .....	D-22
SPZ 1-2 Groove .....	D-9
SPZ 3-4 Groove .....	D-10
SPZ 5-6 Groove .....	D-11
SPZ 8 Groove .....	D-12
V-Belt Dynamic Balancing .....	D-29
V-Belt Installation/Tensioning .....	D-32 – D-33
Volume Equivalents .....	G-26 - G-27

ITEM	PAGE
<b>W</b>	
Watt Conversion .....	G-24
Weld-On Hubs	
QD .....	B-4 - B-7
Taper Bushed .....	B-9 - B-14

# Warning & Safety Reminder

The Martin logo is displayed in a stylized, white, cursive font on a black rectangular background.

## WARNING & SAFETY REMINDER

Safety must be considered a basic factor in machinery operation at all times. Most accidents are the result of carelessness or negligence. All rotating power transmission products are potentially dangerous and must be guarded by the contractor, installer, purchaser, owner, and user as required by applicable laws, regulations, standards, and good safety practice. Additional specific information must be obtained from your local authorities; other sources may include the latest editions of American Society of Mechanical Engineers at 345 East 47th Street, New York, NY 10017 (+1-212-705-7722)

It is the responsibility of the contractor, installer, purchaser, owner, and user to install, maintain, and operate the parts or components manufactured or supplied by *Martin* Sprocket & Gear, Inc., in such a manner as to comply with the requirements of your local laws, ordinances, regulations, authorities, and safety acts which are similar in spirit and intention of the Williams-Steiger Occupational Safety Act in the USA as well as the American National Standard Institute Safety Code.

## CAUTION

Guards, access doors, and covers must be securely fastened before operating any equipment.

If parts are to be inspected, cleaned, observed, or general maintenance performed, the following precautions must be taken.

1. Isolate the power source from the equipment.
2. Disconnect or reconnect any equipment only if the construction is fully visible and understood.
3. Wear eye protection.
4. Wear appropriate protective clothing, hats, gloves and safety shoes as warranted by the circumstances.
5. Check that all tools are used in good working condition only.
6. Loosen tensioning devices carefully.
7. Avoid sudden and unexpected movement of parts of the equipment and/or components.
8. Do not reuse individual components.
9. Do not reuse a damaged or faulty part.

Failure to follow these measures may result in personal injury or property damage.

## WARNING

### NOTE: CATALOG DIMENSIONS

Every effort is made to keep all catalog dimensions and styles current in the catalog. However, from time to time it is necessary because of manufacturing changes to alter stock products dimensionally.

If any stock product dimension or style shown in this catalog is critical to your application please consult factory for verification.